



India's Most Trusted CCTV Brand

UC-4G 4M-PT (PL)

4MP 4G Mini Pan-Tilt ATC Camera



FEATURES

- 4MP (2688 x 1520) Resolution
- All Time Color Vision
- Horizontal Rotation: 255°, Vertical Rotation: 90°
- Support 10x Digital Zoom
- Full Duplex Audio Intercom (Built-in High Sensitivity Mic & Speaker)
- 10 Preset Points for favorite location
- Smart Human Detection, Motion Detection, Motion Tracking
- Mobile Notification on Human & Motion Detection
- Customized Pre-recorded Voice Alarm
- Support Micro SD Card upto 256GB & Cloud Storage(Optional)
- Compatible with all ONVIF Supported NVRs
- QR Code Scanning for Network Connection
- Monitoring: Mobile/PC Software (TrueCloud)
- IP66 Waterproof Rating, 4000 Lightning Protection.
- Alexa Support

www.unicamsystems.com

Technical Specification

Product Code	: UC-4G 4M-PT (PL)
Image Sensor	: 1/2.9" CMOS Sensor
Resolutions	: 4MP (2688 x 1520)
Lens	: 4mm
IR LED	: 12 Array
IR Distance	: 30 Meters
White LED	: 12 White Array
White LED Distance	: 20 Meters
Viewing Angle	: Horizontal: 68°, Vertical: 53°, Diagonal: 81°
Video Streaming	: Main Stream: 2304 x 1296 / 15 fps Sub Stream: 640 x 360 / 15 fps
Audio Input/Output	: Two way audio, Built in microphone and speakers
Audio Compression Standard	: AAC/G711A
Pan-Tilt Angle	: Pan: 0° - 255°, Tilt: 0° - 90° Horizontal speed 20°/S, Vertical Speed 10°/S
Zoom	: 10x Digital
Light Mode	: Full Color / Infrared / Intelligent
DNR	: 3D Digital Noise Reduction
Day & Night	: IR-cut Auto ICR
Min Illumination	: Color: 0.01 Lux, Black & White: 0.001 Lux
White Balance	: Auto
WDR	: D-WDR
Mirror/Flip	: On / Off
Electronic Shutter	: Auto
On Screen Display (OSD)	: Date, Time, & Title
AI Features	: Motion Detection, Human Detection, Human Tracking.
Privacy Zone	: Support 4 Zone
Monitoring	: Andriod, iOS, Windows (EseeCloud)
Protocol	: NI/Onvif
Slots	: 4G Sim Card / Micro SD Card
Storage	: Support Micro SD Card upto 256GB & Cloud Storage (Optional)
Connectors	: RJ45 Port, Reset Button & DC Power Input
Connection Mode	: 4G Sim & Lan Network
4G Frequency Band	: FDD-LTE: B1/B3/B5/B8; TDD-LTE: B34/B38/B39/B40/B41
Light Mode Indication	: LED Blink: Not connected to Network, LED Continuous ON: Connected to Network
Power Input	: DC: 12V/1A (DC 2.1mm Connector)
Power Consumption	: ≤5W
Working Temperature / Humadity	: 0-50° C RH Less than 95% (No Condensation)
Storage Temperature / Humadity	: -20° C to 60° C / 20% to 90% RH
Housing Type	: Plastic (IP66)
Dimension	: 310mm*112mm*170(H x W x L)
Net Weight	: 0.474Kg
Gross Weight	: 0.680Kg