



India's Most Trusted CCTV Brand

UC-4G-IR SL (PL)



All Time
Color Vision



Human
Tracking

10X 
10X
Digital Zoom

4MP 4G

Dome All Time Colour Camera

FEATURES

- 4MP (2688 x 1520) Resolution
- All Time Colour Vision
- Full Duplex Audio Intercom (Built-in High Sensitivity Mic & Speaker)
- Support 10x Digital Zoom
- Area Motion Detection, Humanoid Detection, Push Realtime Notification on the Application
- Mobile Notification on Human & Motion Detection
- Customized Pre-recorded Voice Alarm
- Support Micro SD Card upto 256GB & Cloud Storage(Optional)
- Compression: H.264 / H.265 / H.265+
- 4G connection .QR code for Easy to add camera in the app
- Monitoring: Mobile/PC Software (Eseecloud)
- Alexa Support

Technical Specification

Product Code	: UC-4G-IR SL (PL)
Image Sensor	: 1/2.8" CMOS Sensor
Resolution	: 5MP (2688 x 1520)
Lens	: 4mm
IR LED	: 2 IR Array
IR Distance	: 20 Meters
White LED	: 2 White Array
White LED Distance	: 10 Meters
Min Illumination	: Color: 0.01 Lux, Black & White: 0.001 Lux
Day & Night	: IR-cut Auto ICR
Light Mode	: Full Color / Infrared / Intelligent
Viewing Angle	: Horizontal: 75°, Vertical: 59°, Diagonal: 88°
Video Streaming	: Main Stream: 2304x1296@15fps Sub Stream: 800x448@15fps
Audio Input/Output	: Two way audio, Built in microphone and speakers
Audio Compression Standard	: AAC
Zoom	: 10x Digital
DNR	: 3D Digital Noise Reduction
White Balance	: Auto
WDR	: D-WDR
Mirror/Flip	: On / Off
Electronic Shutter	: Auto
On Screen Display (OSD)	: Date, Time, & Title
AI Features	: Motion Detection, Human Detection.
Privacy Zone	: Support 4 Zone
Monitoring	: Andriod, iOS, Windows (TrueCloud)
Slots	: 4G Sim Card / Micro SD Card
Storage	: Support Micro SD Card upto 256GB & Cloud Storage (Optional)
Communication Protocol	: Private N1/RTMP
Connection Mode	: 4G Sim Network
4G Frequency Band	: FDD-LTE: B1/B3/B5/B8; TDD-LTE: B34/B38/B39/B40/B41
Connectors	: DC Power Input, Reset Button
Power Input	: DC: 12V/1A (DC 2.1mm Connector)
Power Consumption	: ≤ 3W
Working Temperature / Humadity	: 0-50° C RH Less than 95% (No Condensation)
Storage Temperature / Humadity	: -20° C to 60° C / 20% to 90% RH
Housing Type	: Plastic
Dimension	: 86mm X106.5mm X 106.5mm (H x W x L)
Net Weight	: 168 Gms
Gross Weight	: 246 Gms

*Note: Product Specifications are subject to change without prior notice.