



India's Most Trusted CCTV Brand

UC-P425 CI-L

2MP DUAL ILLUMINATION BULLET IP CAMERA



- 2MP (1920 × 1080) H.265 coding
- Max.resolution: 1920 × 1080
- Built-in white light and IR LED; 20-30m IR view distance
10-20m white light view distance
- ICR auto switch, true day / night, ROI coding
- 3D DNR, digital WDR, HLC, BLC, defog
- PoE power supply optional
- IP 67 ingress protection
- Support dual streams
- Support mobile surveillance by smart phones with iOS
and Android OS
- Intelligent analytics: video blur detection, scene change
detection, line crossing detection and region intrusion detection



www.unicamsystems.com

SPECIFICATIONS

Model	UC-P425 CI-L			
Specifications				
Camera				
Image Sensor	1 / 2.8 "CMOS			
Image Size	1920×1080			
Electronic Shutter	1 s ~ 1 / 100000 s			
Iris Type	Fixed Iris			
Min. Illumination	0.0126lux @F1.2, AGC ON; 0 lux with illuminator ON 0.0462 lux @ F2.2, AGC ON; 0 lux with illuminator ON			
Lens	3.6 mm @F2.2, H.FoV: 82.5°, V.FoV: 44.9°, D.FoV: 99.3° 6 mm@F2.0, H.FoV: 52.7°, V.FoV:30.27°, D.FoV: 60.23°			
Lens Mount	M12			
Wide Dynamic Range	Digital WDR			
BLC	Yes			
HLC	Yes			
Defog	Yes			
Digital NR	3D DNR			
Image				
Video Compression	H.265 / H.264			
H.265 Compression Standard	Main Profile@Leve4.1 High Tier			
Resolution	1080P (1920 × 1080), 720P (1280 × 720), D1, CIF			
Main Stream	60Hz : 1080P /720P (1~30fps); 50Hz : 1080P/720P (1~25fps)			
Sub Stream	60Hz : D1/CIF(1~30fps); 50Hz: D1/CIF (1~25fps)			
Bit Rate	64 Kbps ~ 4 Mbps			
Bit Rate Type	VBR / CBR			
Image Settings	ROI, Saturation, Brightness, hue, Contrast,Wide Dynamic, Image Mirror, NR, Image Flip, Sharpness, etc. adjustable through client software or web browser			
ROI	Each ROI to be configured separately			
Interfaces				
Network	RJ45			
Video Output	No			
Audio	No			
Storage	No			
Reset	No			
Functions				
Remote Monitoring	Web Browser/TVT NVMS2.0/NVR/mobile APP			
Online Connection	Support simultaneous monitoring for up to 3 users; Support multi-stream real time transmission			
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, 802.1x, UPnP, HTTP, HTTPS, QoS			
Interface Protocol	ONVIF			
Storage	Network remote storage			
Smart Alarm	Motion detection			
Intelligent Analytics	Region intrusion detection, video blur detection, scene change detection and line crossing detection			
General Function	Watermark, IP address filtering, video mask, heartbeat, illegal login lock			
PoE	Optional (IEEE802.3af)			
Supplement Light Range	White light Range:10~20m IR Range: 20~30			
Ingress Protection	IP67			
DORI Distance				
Lens	Detect	Observe	Recognize	Identify
3.6mm	52.28m(171.52ft)	20.91m(68.6ft)	10.46m(34.31ft)	5.23m(17.15ft)
6mm	79.86m(262.0ft)	31.94m(104.79ft)	15.97m(52.39ft)	7.99m(26.21ft)

Others	
Power Supply	DC12V(PoE power supply optional)
Power Consumption	< 7.5W
Operating Environment	- 20 °C ~ 55 °C (-4°F~131°F); Humidity: less than95 % (non-condensing)
Storage Environment	- 20 °C ~ 60 °C (-4°F~140°F); Humidity: less than95 % (non-condensing)
Dimensions (mm)	169.8× 93.6× 85.7
Weight (net)	Approx.0.257KG
Installation	Wall mounting
Certificate	CE, FCC
Environmental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU) , directive 94/62/EC and REACH(EC1907/2006)

DIMENSIONS
