



India's Most Trusted CCTV Brand

UC-IPC1240-IR SP




*Built-in
Audio*

**4MP NETWORK
IR DOME CAMERA**

www.unicamsystems.com

4MP Network IR Dome Camera



Features

- 4MP (2560 x 1440) coding
- Max. resolution: 2560 x 1440
- ICR auto switch, true day / night
- 10 ~ 20m IR night view distance
- 3D DNR, digital WDR, ROI coding
- PoE power supply
- Smart analytics (optional): abnormal video signal detection, intrusion detection and line crossing detection
- Support smart phone, iPad, remote monitoring
- P2P function optional
- Support three streams

Specifications

Model	UC-IPC1240-IR SP
Specifications	
Camera	
ImageSensor	1 / 3 "CMOS
ImageSize	2560 x 1440
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Auto Iris	Fixed Iris
Min . Illumination	0.06 lux @F2.0,AGC ON; 0 lux with IR
Lens	3.6 mm @ F2.0, horizontal field of view : 72°
LensMount	M12
Day & Night	ICR
Wide Dynamic Range	HWDR
Digital NR	3D DNR
Angle Adjustment	Any angle
Audio	In-Build Audio
Image	
Video Compression	H.264 / H.265 / H.265+
H.264 Compression Standard	Baseline Profile / Main Profile / High Profile
Resolution	4MP (2560 x 1440), 3MP (2048 x 1536), 1080P (1920 x 1080), 720P (1280 x 720), D1, CIF, 480 x 240
Main Stream	60Hz : 3MP (1 ~ 30fps) / 1080P (1 ~ 30fps) / 720P (1 ~ 30fps) 50Hz : 3MP (1 ~ 25fps) / 1080P (1 ~ 25fps) / 720P (1 ~ 25fps)
BitRate	128 Kbps ~ 6 Mbps
EncodeMode	VBR / CBR
Quality	Five levels under VBR; Freely adjustable under CBR
ImageSettings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR,etc. adjustable through client software or web browser
Interfaces	
Network	RJ45
Functions	
RemoteMonitoring	IEbrowsing,CMSremote control
OnlineConnection	Support simultaneous monitoring for up to 4 users ; Support multi-stream real time transmission
Network Protocol	TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Interface Protocol	ONVIF
Storage	Network remote storage
SmartAlarm	Motion alarm
IRDistance	10 - 20 m
Water-proof	NA
Others	
PowerSupply	DC12V / PoE
Power Consumption	< 5W
Operating Environment	- 20°C ~ 50 °C,10% ~ 90% humidity
Dimensions (mm)	Φ 70 × 156
Weight (net)	320 g
Installation	Wall mounting, ceiling mounting