



**UNICAM  
SYSTEMS**  
LEGITIMATE SECURITY GUARANTEED

*India's Most Trusted CCTV Brand*

**UC-IPC1240-L2 SP**



*Built-in Audio*

**4MP NETWORK  
IR BULLET CAMERA**

[www.unicamsystems.com](http://www.unicamsystems.com)

## 4MP Network IR Water-proof Bullet Camera



## Features

- 4MP ( 2560 x 1440 ) coding
- Max. resolution: 2560 x 1440
- ICR auto switch, true day / night
- 10 ~ 20m IR night view distance
- 3D DNR, digital WDR, ROI coding
- PoE power supply
- Smart analytics (optional): abnormal video signal detection, intrusion detection and line crossing detection
- Support smart phone, iPad, remote monitoring
- P2P function optional
- IP67 ingress protection
- Support three streams

## Specifications

| Model                      | UC-IPC1240-L2 SP                                                                                                                           |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Specifications</b>      |                                                                                                                                            |
| <b>Camera</b>              |                                                                                                                                            |
| ImageSensor                | 1 / 3 \"CMOS                                                                                                                               |
| ImageSize                  | 2560 x 1440                                                                                                                                |
| Electronic Shutter         | 1 / 25 s ~ 1 / 100000 s                                                                                                                    |
| Auto Iris                  | Fixed Iris                                                                                                                                 |
| Min . Illumination         | 0.06 lux @F2.0,AGC ON; 0 lux with IR                                                                                                       |
| Lens                       | 3.6 mm @ F2.0, horizontal field of view : 72°<br>( 6 mm optional )                                                                         |
| LensMount                  | M12                                                                                                                                        |
| Day & Night                | ICR                                                                                                                                        |
| Wide Dynamic Range         | HWDR                                                                                                                                       |
| Digital NR                 | 3D DNR                                                                                                                                     |
| Angle Adjustment           | Any angle                                                                                                                                  |
| Audio                      | In-Build Audio                                                                                                                             |
| <b>Image</b>               |                                                                                                                                            |
| Video Compression          | H.264 / H.265 / H.265+                                                                                                                     |
| H.264 Compression Standard | Baseline Profile / Main Profile / High Profile                                                                                             |
| Resolution                 | 4MP (2560 x 1440), 3MP ( 2048 x 1536 ), 1080P ( 1920 x 1080 ), 720P ( 1280 x 720 ), D1, CIF, 480 x 240                                     |
| Main Stream                | 60Hz : 3MP ( 1 ~ 30fps ) / 1080P ( 1 ~ 30fps ) / 720P ( 1 ~ 30fps )<br>50Hz : 3MP ( 1 ~ 25fps ) / 1080P ( 1 ~ 25fps ) / 720P ( 1 ~ 25fps ) |
| BitRate                    | 128 Kbps ~ 6 Mbps                                                                                                                          |
| EncodeMode                 | VBR / CBR                                                                                                                                  |
| Quality                    | Five levels under VBR; Freely adjustable under CBR                                                                                         |
| ImageSettings              | ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR,etc. adjustable through client software or web browser            |
| <b>Interfaces</b>          |                                                                                                                                            |
| Network                    | RJ45                                                                                                                                       |
| <b>Functions</b>           |                                                                                                                                            |
| RemoteMonitoring           | IEbrowsing,CMSremote control                                                                                                               |
| OnlineConnection           | Support simultaneous monitoring for up to 4 users ;<br>Support multi-stream real time transmission                                         |
| Network Protocol           | TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP                                                                                      |
| Interface Protocol         | ONVIF                                                                                                                                      |
| Storage                    | Network remote storage                                                                                                                     |
| SmartAlarm                 | Motion alarm                                                                                                                               |
| IRDistance                 | 10 - 20 m                                                                                                                                  |
| Water-proof                | IP67                                                                                                                                       |
| <b>Others</b>              |                                                                                                                                            |
| PowerSupply                | DC12V / PoE                                                                                                                                |
| Power Consumption          | < 5W                                                                                                                                       |
| Operating Environment      | - 20°C ~ 50 °C,10% ~ 90% humidity                                                                                                          |
| Dimensions ( mm )          | Φ 70 × 156                                                                                                                                 |
| Weight ( net )             | 380 g                                                                                                                                      |
| Installation               | Wall mounting, ceiling mounting                                                                                                            |