



**UNICAM
SYSTEMS**
LEGITIMATE SECURITY GUARANTEED

India's Most Trusted CCTV Brand

UC-P1016-2UG-1SF

16+2 POE 250M LONG DISTANCE

PoE Switch (Built-in)



FEATURES

- 16*10/100Mbps POE port;2*100/1000Mbps UP Link;
- 250m Distance;Vlan support
- Support IEEE802.3AF/AT
- Whole Power:250W(52V 4.8A)
- All port supported by MDI/MDIX auto flip and self negotiation
- Supply 18 10/100/1000Mbps adaptive high speed forwarding data packet non-lost port.
- Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode.
- Each port max. power supply reached 30W.

Application:

- Wireless Access Point
- IP Camera
- IP Phone
- Computer Networks

www.unicamsystems.com

SPECIFICATIONS

Product	16+2 port 250m POE switch(Built-in)
Model	UC-P1016-2UG-1SF
POE Port	1 to 16 port support IEEE802.3af/at
UP link port	17th-18th port support 1000Mbps
Output Power	15.4W/30W IEEE802.3af/at
Power Pin	1/2+, 3/6-
Whole Power	≤250W
POE Protocol	IEEE 802.3af/IEEE 802.3at
POE Type	End-span
Power Distance	≤250m
Network Standard	IEEE 802.3、IEEE802.3u、802.3x、802.3af/at
Network Medium	100/1000BASE-TX: 5 class and above non shielded twisted pair
Data Distance	≤250M
Switch Capability	12Gbps
Forwarding Mode	Store and forward
Forwarding Rate	100Mbps:14880pps, 1000Mbps:14800pps, 1000BASE-T: 1488095pps/port
MAC Address	2K MAC address table
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	LINK/ACT. 100Mbps;POE Status indicator; POWER indicator;EXTENDER indicator
Working Environment	Working temperature: -10°-- 55°C
Input power	AC100-240V 50/60HZ
Weight	2.1kg
Size	270mm*180mm*44mm(L*W*H)