



India's Most Trusted CCTV Brand

Smart 4MP WiFi

Mini PT Camera Night View



4 MP
Resolutions



Cloud
Recording



2 Way Audio
Intercom



Wi-Fi



256GB
SD Card



Auto Human
Tracking



Works
with Alexa



All Time
Color Vision

UC-WF-4M-PT (PL)

4MP Outdoor PT Camera with Colorized Night View

FEATURES

- Pan/tilt Smart Mini PT Wi-Fi Camera
- Horizontal rotation of 263 degrees, vertical rotation of 90 degrees
- Built-in high-sensitivity MIC and speaker, support two-way audio
- Intelligent Human tracking, automatically tracking when people break area
- Support Micro SD Card Upto 256GB & Cloud Storage (Optional)
- Wi-Fi & Wired connection, scan the QR code to easily connect the camera
- Area motion detection, Humanoid detection, push alarm information
- Upto to 8 preset point to monitor favorite locations
- Compression : H.264/H.265/H.265+



Infrared mode



Full-color mode



Technical Specification

Model Number	:	UC-WF-4M-PT (PL)
Image Sensor	:	1/3" CMOS Sensor
Resolutions	:	4MP: 2688 × 1520
Video Compression Standard	:	H.264/H.265/H.265+
Lens	:	4mm @ F2.O, View Angle : 68° (Horizontal), 81° (Diagonal)
IR LED	:	4 LED
IR distance	:	30 Meter
White LED	:	4 LED
White Distance	:	20 Meter
Video Encode Stream	:	Main Stream : 2688 × 1520 \ 15FPS; Sub Stream : 640 x 360 \ 15FPS
Light Mode	:	Full color / Infrared / Intelligent
Audio Input \ Output	:	Supports Two-way Audio, Built-in Microphone and Speaker
PTZ Rotation Range	:	Horizontal 263° 0.1°-20°/sec, Vertical 90° 0.10-20°/sec
Minimum Illumination	:	Color: 0.01Lux, Black and White: 0.001 Lux
Audio Compression Standard	:	AAC/G711A
WDR	:	Support DWDR
Electronic Shutter	:	Auto
Wi-Fi	:	IEEE802.11b, 802.11g, 802.11n
Frequency Range	:	2.4 GHz – 2.4835 Ghz
Security	:	64/128-bit WEB, WPA/WPA2, WPA-PSK/WPA2-PSK
Rj45 Network Port	:	RJ45 X 1(10M/100M Adaptive Ethernet Port)
Alarm	:	1Motion Detection, Alarm Picture Push 2 Human Detection
Monitoring	:	Android & Iphone / Windows PC (EasyCloud)
Storage	:	Support Micro SD Card (Max 256GB)
Protocol	:	Proprietary Protocol NI/Onvif/RTSP
Power	:	DC12V/1A
Power Consumption	:	≤15W
Working Temp	:	0-15° RH Less Than 95% (No Condensation)
Storage Temperature/Humidity	:	-20° to 60° / 20% to 90% RH
Housing Type	:	Plastic (IP66)